

MINI 15



www.ommelift.dk

BIG FEATURES – LIGHT AND EASY TRAILER MOUNTED

OMME LIFT A/S – Lægårdsvej 4 – DK 7260 Sdr. Omme
Phone: + 45 753 413 00 – Fax: + 45 753 415 92
E-mail: omme@ommelift.dk – Web: www.ommelift.dk


OMMELIFT



Quality since 1906

Mini 15 E

Mounted on trailer



Technical data:	Mini 15 EXJ	Mini 15 EBXJ
Max. working height	14.60 m	
Max. outreach	8.27 m	
Max. basket load	125 kg	
Basket size	0.85x0.7x1.1m	
Rotation	± 355°	
Power supply	230V/10A	24V/139Ah/5h
Transport length	6.05 m	
Transport height	1.94 m	
Transport width	1.50/1.05 m	
Operational width	3.63 m	
Total weight aprox.	1500 kg	1500 kg
230 V outlet in basket	+	
2 – step controls	+	
Adjustable travelling width	+	
Propulsion	+	

+ standard

BIG FEATURES – LIGHT AND EASY



Easy transport



Narrow



Propulsion



Fly jib

- Type 15 EXJ is powered by 230V mains and is especially suitable where continuous operation is required. Type 15 EBXJ is also powered by a heavy duty 24V/139 Ah battery pack with built-in charger capable of charging the batteries whilst the platform is in use. Operation is also possible independently of mains connection. Weighing only 1500 kg it is towable by cars and smaller vans.
- With the axles retracted, the overall width is down to 1.05 m which enables the lift to pass through narrow openings. Standard features also include hydraulic stabilizers, tool tray and power outlet in the basket. Easy to operate controls are available in the basket and at base. The high and low speed facility gives steady and smooth movements.
- The fly jib provides access up and over roof edges or other difficult to reach areas. The jib also lifts the basket up behind obstacles. Generally, the fly jib means more convenient and precise manoeuvrability.
- The telescopic boom ensures quick up and down movements and enables full unrestricted outreach to be achieved even at low level.